



BARCOL HARDNESS TESTER 936

The Barcol Hardness Tester 936 is a convenient tool for testing the hardness of rubber, wood, leather, and other super soft material.

Barcol hardness tester has simple operation. The specimen is placed under the indenter of the tester and a uniform pressure is applied to the specimen until the dial indication reaches a maximum. The depth of the penetration is converted into absolute Barcol numbers.





FEATURES

- **Easy to use:** No experience required, single hand operation, easy to use. It can be used in any position and in any space that will allow for the operator's hand. The hardness reading is immediately indicated on the dial, which is divided into one hundred graduations.
- **High Sensitivity:** Barcol Hardness Tester has 100 scales. Sensitivity is higher than that of Webster Hardness Testers.
- **Wide testing range:** It can test from pure aluminum to super hard aluminum alloy.
- **Indenter:** The material hardness of indenter and dimensional tolerance are conform to 2013 verification regulation and enterprise internal standard. Strict quality inspection one by one making sure the accuracy of Barcol hardness tester. Long life and good inter convertibility.
- **Screw Rod:** With sophisticated screw machinery structure. Ensure the life and reliability of the instruments are much higher than that of other Barcol Hardness Testers
- **Die cast casing:** Strong and good grip



TECHNICAL SPECIFICATION

Name	Barcol Hardness Tester
Test Range	0-100 HBa (equivalent to 25-135 HBW)
Resolution	0.5 HBa
Indicator Error	± 2 HBa (42-48 HBa)
	± 1 HBa (81-88 HBa)
Repeatability Error	± 2 HBa (42-48 HBa)
	± 1 HBa (81-88 HBa)
Weight	0.5 kg

STANDARD PACKAGE



Tester



2 Spare Indenters



43-48HBa Barcol
Hardness Block



Calibration Wrench



Leg



Carrying Case